

DUAL WALL PIPE

LOW-HEAD IRRIGATION, SANITITE®, BLUE SEAL®, SURE-LOK® ST & HI-Q®

CHARACTERISTICS

PRODUCT	DESCRIPTION	DIAMETER	CONNECTION	SPECIFICATIONS/ PERFORMANCE
LOW-HEAD IRRIGATION	Annular corrugations with HDB rated smooth interior liner. Pipe is bell-and-spigot with the bell being reinforced with a ceramic polymer wrap and the spigot having two gaskets.	30" - 60" * (750-1500mm)	Bell-and-spigot with 2 rubber gaskets meeting ASTM F477.	30" - 60" (750-1500mm) meets ASTM F2306. Joints meet the requirements of ASTM D3212.
SANITITE	Annular corrugations with smooth interior liner. Pipe is bell-and-spigot with the bell being reinforced with a ceramic polymer wrap and the spigot having two gaskets.	30" - 60" * (750-1500mm)	Bell-and-spigot with 2 rubber gaskets meeting ASTM F477.	30" - 60" (750-1500mm) meets ASTM F2306. Joints meet the requirements of ASTM D3212.
BLUE SEAL	Annular corrugations with smooth interior liner. Pipe is bell-and-spigot with the bell being reinforced with a ceramic polymer wrap.	4" - 60" (100-1500mm)	Bell-and-spigot with rubber gasket meeting ASTM F477.	4" - 10" (100-250mm) meets AASHTO M252. 12" - 60" (300-1500mm) meets ASTM F2306 and AASHTO M294, Type S. Joints meet the requirement of ASTM D3212.
SURE-LOK ST	Annular corrugations with smooth interior.	4" - 60" (100-1500mm)	Bell-and-spigot with rubber gasket meeting ASTM F477.	4" - 10" (100-250mm) meets AASHTO M252. 12" - 60" (300-1500mm) meets ASTM F2306 and AASHTO M294, Type S.
HI-Q	Annular corrugations with smooth interior.	4" - 30" (100-750mm)	External snap or split band couplers depending on diameter.	4" - 10" (100-250mm) meets AASHTO M252. 12" - 30" (300-750mm) meets AASHTO M294, Type S.

*Not available in 54"